



ROUGH OPENING NOTE: ACTUAL SIZE WITH THE MECHANISM SITTING WITH THE ENCLOSURE DOWN
 EQUALS 44 1/2 X 46 1/2 (FLANGES REMOVED)
 MINIMUM ROUGH OPENING EQUALS 46 1/2 X 48
 NORMAL ROUGH OPENING IS 48 X 48
 NOTE: FIRE POLE RESTS ON THE FLANGE ON ALL SIDES
 THE FLANGE IS COVERED BY THE FLOOR PLATES
 THE TRIM IS INSTALLED TO COVER THE GAP BETWEEN
 THE SIDE OF THE ROUGH OPENING AND THE BOTTOM OF THE FRAME

APPROXIMATE WEIGHT OF FIRE POLE COMPLETE : 700 POUNDS

NOTE: A FIRE PROOF BARRIER MUST BE IN PLACE TO MAINTAIN THE FIRE RATING.

QTY:

REC	REV	DATE	BY	CHK	APP
	BB/04				

McIntire Brass Works, Inc.
 AUTOMATIC SLIDE POLE
 MODEL 21
 INSTALLATION DIAGRAM
 D 15 AMP 120 VAC SURGE-SUPPRESSED LINE IN (MUST BE A DEDICATED CIRCUIT)
 12" FULL 48" FULL 52" FULL
 LAYOUT A
 1 of 1