



- NOTES:**
1. IT IS IMPORTANT THAT THE CONTRACTOR SHOULD LOCATE THE POLE OPENING IN ACCORDANCE WITH THE MINIMUM DISTANCES SHOWN ON THE SHEET
 2. PLAN TO SET THE POLE SO THAT THE ENTRANCE TO THE CAGE WILL BE LOCATED BETWEEN ANY TWO OF THE THREE STANCHIONS. LOCATE THE GATE IN THE MOST PRACTICAL POSITION FOR QUICK ACCESS.
 3. THE FLOOR MUST BE LEVEL.
 4. FOR INSTALLATION INSTRUCTIONS: SEE DETAILED INFORMATION ON SHEET

| | | | | | | | |
|--------------|--|-----------------|--|---|--------------|-----------------------------------|----------|
| DRAWN EBC | | DATE 3/22/10 | | McIntire Brass Works, Inc. 14 HORACE STREET SOMERVILLE, MA 02143 | | | |
| APPD | | | | AUTOMATIC SLIDE POLE MODEL 22 INSTALLATION DRAWING | | | |
| MATH | | | | SIZE D | DO NOT SCALE | PRCD CODE Websitedrwg Model 22 | REV A |
| FINISH | | | | TOLERANCES-UNLESS SPECIFIED X.XX=0.01 (25MM) XX.XX=0.1 (1.27MM) ANGLE=±5° | | SCALE FULL | |
| | | | | DWG TYPE | | SHEET 1 OF 1 | |